

STOCKY™

RIDER ON ELECTRICAL PALLET TRUCK

HEAVY LIFTER UP TO 3 TON

LOGISTICS HUB MVP

ERGONOMICS WORK DESIGN

ENGINEERED FOR LONG DISTANCE



FOLDABLE PLATFORM



SAFETY ARM SUPPORT

ONE CONTROL PANEL MAXIMUM EFFICIENCY

Emergency reverse

Horn

Lifting & Lowering

Drive control

Turtle speed



**EMERGENCY SWITCH &
BATTERY INDICATOR**



ACCESSORY GUARD

TECHNICAL SPECIFICATION

ITEM		STOCKY PLATFORM PALLET TRUCK S02-SPPT	
Drive Mode		Electrical Drive	
Operator Type		Station Drive	
Load Capacity	kg	2000/ 2500 / 3000	
Load Centre	mm	600	
Net Weight (With Battery)	kg	810	
Wheel Material		PU	
Front Wheel Size	mm	Φ80 × 70	
Rear Wheel Size	mm	Φ115 × 55	
Drive Wheel	mm	Φ250 × 80	
Rear wheel distance , b11	b11, mm	625	
Wheel Base	Y, mm	1500	
Lifting Height	h3, mm	120	
Vehicle Height	h1, mm	1450	
Max Lifted Height	h4, mm	205	
Lowered Height	h13, mm	85	
Overall Length	l1, mm	1930	
Overall Width	b1, mm	820	
Dimension of Fork	s/e/l, mm	50 / 176 / 1150	
Overall Width of Fork	b5, mm	685	560
Minimum Ground Clearance	m2, mm	30	
Aisle Width for Pallet 1000 x 1200 Crossway	mm	2130	
Aisle Width for Pallet 800 x 1200 Crossway		2180	
Minumum Ground Clearance	mm	30	
Turning Radius	Wa ,mm	1750	
Travel Speed Laden / Unladen	km/h	5.5./ 5.8	
Lifting Speed Laden / Unladen	m/s	0.04 / 0.05	
Lowering Speed Laden / Unladen	m/s	0.06 / 0.05	
Max Gradeability Laden / Unladen	%	8 / 20	
Brake Type		Electromagnetic	
Drive Motor Power / Lift Motor Power	kw	1.5 / 1.5 / 2.2 (AC) /2.2	
Battery Capacity	V/Ah	24 /210 (270)	
Battery Weight	kg	200/ 260	
Steering Mode	V/Ah	Electric Steering	
Sound Level at Driver (EN 12053)	dB (A)	<70	

