STOCKY™

ALL TERRAIN PALLET TRUCK

HEAVY 3-TON CLIMBING POWER

ONE TRUCK FOR ALL SURFACES

BUILT FOR TOUGH JOB SITES





WEATHER PROOF STEEL PROTECTION FRAME



IMPACT-ARMORED & SEALED POWERTRAIN





ALL-TERRAIN CHASSIS & HIGH GROUND CLEARANCE

Technical Parameter

Features						
1.1	Brand		**STOCKY**	**STOCKY**	**STOCKY**	**STOCKY**
1.2	Stock Code		S02-ATPT30SE	S02-ATPT30NR	S02-ATPT30SE-LI	S02-ATPT30NR-LI
1.3	Model		Absorbent Glass Mat (AGM)		Lithium Battery	
1.4	Power Form		Electrical			
1.5	Operation		Walkie			
1.6	Load	kg	3000			
1.7	Load Centre Distance	mm	600			
1.8	Wheelbase	mm	1230/1300			
Weight						
2.1	Truck Weight (With Battery)	kg	230		207	
Wheel						
3.1	Wheel Type		Front Rubber Rear PU / Nylon		Front Rubber Rear PU / Nylon	
3.2	Driving Wheel Size (Diameter x Width)	mm	Φ350 x 100		Φ350 x 100	
3.3	Load Bearing Wheel Size (Diameter x Width)	mm	Φ80 x 60		Φ80 x 60	
3.4	Number Wheel Drive Side / Load Side		1 / 4		1 / 4	
3.5	Drive Wheel / Supporting Wheel Number (x = Drive Wheel)	mm	2 x /2		2 x /2	
Basic Size						
4.1	Maximum Height of Fork	mm	200		200	
4.2	Lifting Stroke	mm	115		115	
4.3	Minimum Height of Fork (+/- 2mm)	mm	85		85	
4.4	Fork Outer Distance	mm	550	685	550	685
4.5	Fork Inner Distance	mm	250	385	250	385
4.6	Length of Fork	mm	1150	1220	1150	1220
4.7	Width of Forks	mm	150		150	
4.8	Thickness of Forks	mm	60		60	
4.9	Overall Width	mm	595	685	595	685
4.10	Overall Height Without Handle	mm	800		800	
4.11	Overall Length	mm	1780	1850	1780	1850
4.12	Overall Height With Handle	mm	1260		1260	
4.13	Turning Radius	mm	1550	1620	1550	1620
Capability						
5.1	Travel Speed (Laden/Unladen)	km / h	4 / 4.5		4 / 4.5	
5.2	Lifting Speed (Laden/Unladen)	mm/s	15 / 19		15 / 19	
5.3	Maximum Climbing Grade (Laden/Unladen)	%	8 / 16		8 / 16	
5.5	Brake Type		Electromagnetic Brake		Electromagnetic Brake	
Motor						
6.1	Rated power of Driving Motor	kw	1.0		1.0	
6.2	Rated power of Lifting Motor	kw	0.8		0.8	
6.3	Battery	V / Ah	48/32		51.2/30	
6.4	Battery Weight	kg	36		12.5	

APPLICATION



OUTDOOR
CONSTRUCTION SITE



FACTORY
MATERIAL HANDLING

STOCKY™

COLD ROOM PALLET TRUCK

HEAVY DUTY 3 TON CAPACITY

SAFE HEAVY LIFTING ON ICY FLOORS

ELIMINATE COLD-ROOM DOWNTIME





SEALED CONNECTOR FOR LOW-TEMPERATURE POWER EFFICIENCY



FULLY SEALED PROTECTION ON GEAR



STABLE HANDLING ON SLIPPERY SURFACE

Technical Parameter

Features				
1.1	Brand		**STOCKY**	**STOCKY**
1.2	Stock Code		S02-CRPT30SE	S02-CRPT30NR
1.3	Model		Absorbent Glass Mat (AGM)	
1.4	Power Form		Electrical	
1.5	Operation		Walkie	
1.6	Load	kg	3000	
1.7	Load Centre Distance	mm	600	
1.8	Wheelbase	mm	1230/1300	
Weight				
2.1	Truck Weight (With Battery)	kg	232	
Wheel				
3.1	Wheel Type		Front Rubber Rear PU / Nylon	
3.2	Driving Wheel Size (Diameter x Width)	mm	Φ350 x 100	
3.3	Load Bearing Wheel Size (Diameter x Width)	mm	Φ80 x 60	
3.4	Number Wheel Drive Side / Load Side		1 / 4	
Basic Size				
4.1	Maximum Height of Fork	mm	200	
4.2	Lifting Stroke	mm	115	
4.3	Minimum Height of Fork (+/- 2mm)	mm	85	
4.4	Fork Outer Distance	mm	550	685
4.5	Fork Inner Distance	mm	250	385
4.6	Length of Fork	mm	1150	1220
4.7	Width of Forks	mm	150	
4.8	Thickness of Forks	mm	60	
4.9	Overall Width	mm	595	685
4.10	Overall Height Without Handle	mm	800	
4.11	Overall Length	mm	1780	1850
4.12	Overall Height With Handle	mm	1280	
4.13	Turning Radius	mm	1550	1620
Capability				
5.1	Travel Speed (Laden/Unladen)	km / h	4 / 4.5	
5.2	Lifting Speed (Laden/Unladen)	mm/s	15 / 19	
5.3	Maximum Climbing Grade (Laden/Unladen)	%	8 / 16	
5.5	Brake Type		Electromagnetic Brake	
Motor				
6.1	Rated power of Driving Motor	kw	1.0	
6.2	Rated power of Lifting Motor	kw	0.8	
6.3	Battery	V / Ah	48/32	
6.4	Battery Weight	kg	36	

APPLICATION



COLD ROOM



FOOD FACTORIES